# NSN 5935-00-493-1412

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-1412 **Body Style:** Right angle type **Overall Length:** 3.969 inches **Overall Width:** 0.656 inches **Body Height:** 0.470 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers:** 3.625 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

# NSN 5935-00-493-1412

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, type mdg military specification single material response single mating end

## **Included Contact Quantity:**

29 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

0.029 gold grains, troy and 0.029 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.