Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-1420

Body Style:
Straight shape
Overall Length:
3.844 inches
Overall Height:
0.609 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Distance Between Mounting Facility Centers:
3.438 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
23 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1575.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
2175.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate

NSN 5935-00-493-1420

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 23 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.023 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.