Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-1427

Body Style:
Right angle type
Overall Length:
3.438 inches
Overall Height:
0.656 inches
Overall Width:
0.719 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Distance Between Mounting Facility Centers:
3.344 inches
Board Accommodated Width:
0.125 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
23 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
725.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
2175.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping



Alum	ninum alloy
	Il Surface Treatment:
	mium and iridium
	Il Material Specification:
	a-591 federal specification single material response
-	rt Material Specification:
	n-14, type mdg military specification single material response single mating end
	Il Guide Type And Location Designator:
	n and m pin
	uded Contact Quantity:
	ingle mating end single contact grouping
Inclu	uded Contact Type:
Rour	nd pin single mating end single contact grouping
Prec	cious Material And Location:
Cont	act surfaces gold and shell surface iridium
Prec	ious Material And Weight:
0.02	3 gold grains, troy and 0.100 iridium grains, troy
Prec	cious Material:
Gold	l and iridium
Shel	If Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
A039	960
Mil-s	std (military Standard):
Mil-n	n-14 spec.