## NSN 5935-00-493-3082

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-3082 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Press fit **Overall Length:** Between 0.860 inches and 0.900 inches **Body Length:** 0.750 inches **Overall Diameter:** Between 0.290 inches and 0.330 inches **Bushing Accommodation Hole Shape:** Round w/flat **Maximum Voltage Rating In Volts:** 1500.0 dc **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.099 inches and 0.109 inches single finger **Finger Accommodation Length:** 0.370 inches and 0.410 inches single finger **Bushing Thru-hole Accommodation Length:** 0.234 inches **Bushing Thru-hole Accommodation Width:** 0.250 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Terminal Type:** Turret

Material:

Plastic, polycarbonate insulator

## NSN 5935-00-493-3082

Tip Jack - Page 2 of 2



Material:
Plastic polycarbonate insulator
<b>Precious Material And Location:</b>
Contact surface gold
Precious Material:
Gold
Surface Treatment:
Gold and nickel contact
Surface Treatment:
Gold contact and nickel contact
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03400