

View Online at https://aerobasegroup.com/nsn/5935-00-493-3513

| Thread Class: |
|---|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Rectangular shape |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.421 inches |
| Overall Height: |
| 1.100 inches |
| Overall Width: |
| 1.450 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.468 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Shell Material Specification: |
| Qq-a-250 federal specification single material response |
| Insert Material Specification: |

Mil-m-14, ty sdg-f military specification single material response single mating end



Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.