Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-5933

Body Style:
Straight shape
Overall Length:
4.469 inches
Overall Height:
0.609 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Distance Between Mounting Facility Centers:
4.063 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
29 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1575.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
2175.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate

NSN 5935-00-493-5933

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.