

View Online at <https://aerobasegroup.com/nsn/5935-00-493-6111>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.203 inches and 1.235 inches

Overall Diameter:

0.750 inches

Cable Entrance Diameter:

Between 0.145 inches and 0.155 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

120.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, d comp ht federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and nickel

Shell Material Specification:

Mil-b-16522 military specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-b-16522 spec.