

NSN 5935-00-493-6132 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-493-6132 **Thread Class:** 2a **Thread Direction:** 

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.060 inches

Right-hand

**Overall Diameter:** 

Between 0.745 inches and 0.755 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.785 inches and 0.795 inches

**Threaded Device Type:** 

Mounting bushing

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

120.0 and 240.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Connector Cable Strain Relief Method:** 

Crimp type

**Thread Size:** 

0.438 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Insert Material:** 

Plastic tetrafluoroethylene single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530, cond h federal specification single material response single mating end single contact grouping

## NSN 5935-00-493-6132

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Material Specification:
Qq-b-626, comp 22 federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0