NSN 5935-00-493-6133

Thread Class:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-6133

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.060 inches
Overall Diameter:
Between 0.745 inches and 0.755 inches
Distance From Mounting Shoulder To Front Face:
Between 0.785 inches and 0.795 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
120.0 and 240.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Crimp type
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:

Qq-c-530, cond h federal specification single material response single mating end single contact grouping

NSN 5935-00-493-6133

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Material Specification:
Qq-b-626, comp 360 federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0