NSN 5935-00-494-6854

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-494-6854 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, thru-hole mount, external coupling **Overall Length:** 2.343 inches **Overall Diameter:** 1.687 inches **Distance From Mounting Shoulder To Front Face:** 0.906 inches **Mounting Facility Thickness:** 0.469 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 3 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.437 inches Thready Qty Per Inch (tpi): 12 **Thread Size:** 1.688 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-494-6854 Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Criticality Code Justification:
Zzzx
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Nickel alloy
Shell Material Specification:
Qq-n-281 classa federal specification single material response
Insert Material Specification:
Mil-p-17091 military specification single material response single mating end
Included Contact Quantity:
3 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Un
Departure From Cited Designator:
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-p-17091 spec.