NSN 5935-00-494-8399

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-494-8399 **Thread Class:** 2a **Thread Direction:** Right-hand **Environmental Protection:** Moisture resistant and salt water resistant **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 18-11 single mating end **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid Thread Length: 1.166 inches **Thread Size:** 1.125 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Included Contact Quantity:** 5 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping Furnished items - mounting nut

Round socket single mating
Special Features:
Furnished items - mounting
Thread Series Designator:
Unef

NSN 5935-00-494-8399

Electrical Receptacle Connector - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0