

View Online at <https://aerobasegroup.com/nsn/5935-00-495-0789>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.015 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Environmental Protection:

Vibration resistant and shock resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.104 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.335 inches and 0.345 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.335 inches and 0.345 inches

Distance From Mounting Shoulder To Front Face:

0.310 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end or rubber synthetic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 11, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Stainless steel or copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 type 11, cl 2 military specification single treatment response

Shell Material Specification:

Qq-s-763 military specification 1st material response or qq-s-764 military specification 1st material response or qq-b-626 federal specification 2nd material response

Insert Material Specification:

Mil-p-19468 military specification 1st material response single mating end or zz-r-765 federal specification 2nd material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Modified terminal

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204