Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-495-4872

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.875 inches
Overall Height:
Between 1.594 inches and 1.656 inches
Overall Width:
Between 1.594 inches and 1.656 inches
Environmental Protection:
Heat resistant and moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.172 inches and 0.187 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.245 inches and 1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.245 inches and 1.255 inches
Distance From Mounting Shoulder To Front Face:
Between 0.750 inches and 0.781 inches
Threaded Device Type:
Coupling facility and back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
22-14 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches and 0.375 inches
Thread Size:
1.375 inches and 1.188 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Material Specification:
Qq-p-416, type 2 class c federal specification single material response
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0