

View Online at <https://aerobasegroup.com/nsn/5935-00-496-3157>

Body Style:

Straight shape

Overall Length:

1.511 inches

Overall Height:

3.111 inches

Overall Width:

3.860 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.112 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.296 inches

Distance From Mounting Shoulder To Front Face:

0.766 inches

Mating End Quantity:

4

Contact Position Arrangement Style:

67 4th mating end

Contact Removability:

Removable 3rd mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

400.0 4th mating end all contact groupings

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -54.2 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back 4th mating end all contact groupings

Contact Material:

Copper alloy 4th mating end all contact groupings

Contact Surface Treatment:

Gold 2nd mating end single contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response 3rd mating end all contact groupings

Terminal Type:

Crimp 4th mating end all contact groupings

Guide Design And Location:

Hexagon shape male post left-hand at 12 oclock and hexagon shape male post right-hand at 12 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification all treatment responses

Included Contact Quantity:

64 4th mating end 2nd contact grouping

Included Contact Type:

Round socket 3rd mating end all contact groupings

Special Features:

Float mount

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.370 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.