NSN 5935-00-496-3261

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-496-3261

Body Style:
Straight shape
Overall Length:
1.511 inches
Overall Height:
3.111 inches
Overall Width:
2.001 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.112 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
W8 2nd mating end
Contact Removability:
Removable 2nd mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 2nd mating end single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -54.2 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back 1st mating end all contact groupings
Contact Material:
Copper alloy 2nd mating end single contact grouping
Contact Surface Treatment:
Gold 2nd mating end single contact grouping
Insert Material:

Plastic all mating ends

NSN 5935-00-496-3261

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response 2nd mating end single contact grouping

Terminal Type:

Crimp 1st mating end all contact groupings

Guide Design And Location:

Hexagon shape male post left-hand at 12 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification all treatment responses

Included Contact Quantity:

8 2nd mating end single contact grouping

Included Contact Type:

Round socket 1st mating end 3rd contact grouping

Special Features:

Float mounts

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.072 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.