NSN 5935-00-496-3292

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-496-3292

Body Style:
Straight shape
Overall Length:
1.511 inches
Overall Height:
3.111 inches
Overall Width:
3.860 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.112 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
3.296 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
4
Contact Position Arrangement Style:
"106, a106" all mating ends
Contact Removability:
Removable all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
400.0 all mating ends single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -54.2 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back all mating ends single contact grouping
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:

Plastic all mating ends

NSN 5935-00-496-3292

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp all mating ends single contact grouping

Guide Design And Location:

Hexagon shape male post left-hand at 10: 30 oclock

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification all treatment responses

Included Contact Quantity:

106 all mating ends single contact grouping

Included Contact Type:

Round pin all mating ends single contact grouping

Special Features:

Float mount

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.424 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.