Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-496-7408

| Thread Class: | |
|---|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape, external coupling | |
| Overall Length: | |
| 0.988 inches | |
| Overall Height: | |
| Between 1.546 inches and 1.578 inches | |
| Overall Width: | |
| Between 1.546 inches and 1.578 inches | |
| Unthreaded Mounting Hole Diameter: | |
| Between 0.115 inches and 0.125 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| Between 1.245 inches and 1.255 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | |
| Between 1.245 inches and 1.255 inches | |
| Distance From Mounting Shoulder To Front Face: | |
| Between 0.469 inches and 0.479 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 22-55 single mating end | |
| Contact Removability: | |
| Nonremovable single mating end single contact grouping | |
| Contact Maximum Current Rating In Amps: | |
| 7.5 single mating end single contact grouping | |
| Contact Maximum Ac Voltage Rating In Volts: | |
| 500.0 single mating end single contact grouping | |
| Contact Maximum Dc Voltage Rating In Volts: | |
| 700.0 single mating end single contact grouping | |
| Polarization Method: | |
| Keyway or multiple keyway | |
| Insert Position In Deg: | |
| 314.0 | |
| Shell Type: | |
| Solid | |
| Connector Locking Method: | |
| Externally threaded shell | |
| | |

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi): 10 Thread Size: 1.375 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.055 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0