NSN 5935-00-496-9345

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-496-9345

Body Style:
Straight shape
Overall Length:
3.218 inches
Overall Height:
0.670 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
2.812 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping or nickel single mating end single contact grouping and gold single mating end single
contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Turret single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium

NSN 5935-00-496-9345

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Precious Material And Weight:

0.011 silver grains, troy and 0.011 gold grains, troy

Precious Material:

Silver and gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.