Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-497-4266

# Body Style:

Straight shape

# Overall Length:

Between 2.714 inches and 2.744 inches

# **Overall Height:**

0.663 inches

#### **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

"c, 27w2" single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

# Polarization Method:

Mating end

Shell Type:

Solid

#### **Connector Locking Method:**

Spring friction

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Silver single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Steel

### Shell Surface Treatment:

Cadmium

#### **Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response single mating end

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

25 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces silver

# **Precious Material And Weight:**

0.025 silver grains, troy

### **Precious Material:**

Silver

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

### Mil-std (military Standard):

Mil-m-19833 spec.