

View Online at <https://aerobasegroup.com/nsn/5935-00-497-7585>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

Between 4.910 inches and 4.940 inches

**Overall Height:**

Between 1.265 inches and 1.290 inches

**Overall Width:**

Between 0.357 inches and 0.373 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.128 inches and 0.144 inches

**Distance Between Mounting Facility Centers:**

Between 4.617 inches and 4.633 inches

**Board Accommodated Length:**

4.192 inches all boards

**Mounting Facility Thickness:**

Between 4.192 inches and 4.208 inches

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

80 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.080 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0