Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-497-9083

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.047 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter: 0.140 inches
Center To Center Distance Between Mounting Facilities Parallel To Height: 0.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material: Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530, comp ht federal specification single material response single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Silver **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Insert Material Specification:** Mil-p-19468 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19468 spec.