Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-4323

### **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

3.312 inches

## **Overall Height:**

0.436 inches

## **Overall Width:**

0.328 inches

#### **Environmental Protection:**

Moisture resistant

### **Distance Between Mounting Facility Centers:**

3.062 inches

### **Board Accommodated Length:**

2.570 inches single board

### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

### Mating End Quantity:

1

### Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

### Contact Removability:

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

### **Polarization Method:**

Contact to contact polarizing keys

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Pin single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

### Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

# Included Contact Quantity:

50 single mating end single contact grouping



Included Contact Type: Bifurcated spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.