## NSN 5935-00-498-5418

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-5418 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 3.280 inches **Overall Height:** 1.040 inches **Overall Width:** 2.380 inches **Cable Entrance Diameter:** Between 0.938 inches and 1.064 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-104 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## **NSN 5935-00-498-5418**Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Criticality Code Justification:
Feat
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Shell Guide Type And Location Designator:
A slot
Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Polarized at position a
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.104 gold grains, troy
Precious Material:
Gold
Test Data Document:
12217-1163014+29 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.