NSN 5935-00-498-5498

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-5498

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
4.300 inches
Overall Height:
0.415 inches
Overall Width:
0.360 inches
Body Height:
0.360 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Distance Between Mounting Facility Centers:
4.000 inches
Threaded Device Type:
Mounting hole
Mounting hole Mating End Quantity:
·
Mating End Quantity:
Mating End Quantity:
Mating End Quantity: 1 Contact Position Arrangement Style:
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability:
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method:
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Guide pin/socket
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Guide pin/socket Thread Size:
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Guide pin/socket Thread Size: 0.112 inches
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Guide pin/socket Thread Size: 0.112 inches Terminal Location:

Insert Material:

Plastic single mating end

Contact Surface Treatment:

Contact Surface Treatment Specification:

Gold single mating end single contact grouping

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

NSN 5935-00-498-5498

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:	
Pin single mating end single contact grouping	
Contact Material Specification:	
Qq-b-750, comp a, hard federal specification single material response single mating en	nd single contact grouping
Included Contact Quantity:	
37 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
C0ntact surfaces gold	
Precious Material And Weight:	
0.037 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	