## NSN 5935-00-498-5520

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-5520

**Body Style:** 

Straight shape, internal coupling w/strain relief

**Body Length:** 

Between 2.214 inches and 2.224 inches

**Overall Diameter:** 

Between 1.479 inches and 1.489 inches

**Environmental Protection:** 

Vibration resistant and moisture resistant and thermal shock resistant

**Cable Entrance Diameter:** 

Between 0.625 inches and 0.750 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

3719p single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.5 2nd mating end all contact groupings

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

50.0

Shell Type:

Solid

**Connector Locking Method:** 

Ball

**Connector Cable Strain Relief Method:** 

Cable clamp

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:** 

Plastic silicone single mating end

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum

**Shell Surface Treatment:** 

Cadmium

# NSN 5935-00-498-5520

Electrical Plug Connector - Page 2 of 2



#### **Included Contact Quantity:**

6 single mating end 1st contact grouping

#### **Included Contact Type:**

Round pin single mating end 2nd contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.043 gold grains, troy and 0.043 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0