NSN 5935-00-498-5664

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-5664

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length: 2.610 inches
Overall Height: 0.305 inches
Overall Width:
0.780 inches
Distance Between Mounting Facility Centers:
2.226 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1 Contact Booking Assessment Style:
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

19 single mating end single contact grouping

NSN 5935-00-498-5664

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.019 silver grains, troy and 0.019 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:

Unc Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.