NSN 5935-00-498-5768

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-5768 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.734 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Environmental Protection:** Corrosion resistant and moisture resistant and sand resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14s-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

NSN 5935-00-498-5768

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
20
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.004 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0