# NSN 5935-00-498-8537

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-498-8537

**Body Style:** 

Straight shape, external coupling w/backshell

**Overall Length:** 

1.552 inches

**Overall Height:** 

1.532 inches

**Overall Width:** 

1.532 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.462 inches and 0.493 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

18-32 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum

**Shell Surface Treatment:** 

Cadmium

# NSN 5935-00-498-8537

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Included Contact Quantity:**

32 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

### **Special Features:**

Four 0.150 in. Diameter intersected mtg holes spaced 1.203 in. By 1.203 in.

#### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-26482 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0