NSN 5935-00-499-8973

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-499-8973

Body Style: Straight shape **Overall Length:** Between 2.714 inches and 2.744 inches Overall Width: Between 0.248 inches and 0.419 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 2.495 inches and 2.505 inches **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and copper single mating end single contact grouping **Insert Material:** Glass and plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, grade c military specification 1st treatment response and mil-c-14550, class 4 military specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Shell Material Specification:

Qq-s-698 federal specification single material response

NSN 5935-00-499-8973

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - bracket

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.