NSN 5935-00-500-5124

Connector Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-500-5124

Overall Length: 3.250 inches Overall Diameter: 2.250 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.173 inches Center To Center Distance Between Mounting Facilities Parallog 2.375 inches Distance Between Centerlines Of Mounting Facilities Parallog 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a Unit Of Measure: v/a	
 2.250 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.173 inches Center To Center Distance Between Mounting Facilities Paralle 2.375 inches Distance Between Centerlines Of Mounting Facilities Paralle 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a 	
Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.173 inches Center To Center Distance Between Mounting Facilities Paralle 2.375 inches Distance Between Centerlines Of Mounting Facilities Paralle 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Pressure proof Unthreaded Mounting Hole Diameter: 0.173 inches Center To Center Distance Between Mounting Facilities Paralle 2.375 inches Distance Between Centerlines Of Mounting Facilities Paralle 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Unthreaded Mounting Hole Diameter:0.173 inchesCenter To Center Distance Between Mounting Facilities Paral2.375 inchesDistance Between Centerlines Of Mounting Facilities Parall2.375 inchesMating End Quantity:2Contact Removability:Nonremovable all mating ends single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 all mating ends single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 all mating ends single contact groupingConnector Locking Method:Bayonet latchInsert Material:PlasticPlasticIncluded Contact Quantity:63 2nd mating end all contact groupingsIncluded Contact Type:Round socket all mating ends single contact groupingKeine Katterial:PlasticIncluded Contact Type:Round socket all mating ends single contact groupingIncluded Contact Type:Round socket all mating ends single contact groupingShelf Life:N/a	
Unthreaded Mounting Hole Diameter:0.173 inchesCenter To Center Distance Between Mounting Facilities Paral2.375 inchesDistance Between Centerlines Of Mounting Facilities Parall2.375 inchesMating End Quantity:2Contact Removability:Nonremovable all mating ends single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 all mating ends single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 all mating ends single contact groupingConnector Locking Method:Bayonet latchInsert Material:Plastic all mating endsShell Material:PlasticIncluded Contact Quantity:63 2nd mating end all contact groupingsIncluded Contact Type:Round socket all mating ends single contact groupingKeint file:N/a	
0.173 inches Center To Center Distance Between Mounting Facilities Paralle 2.375 inches Distance Between Centerlines Of Mounting Facilities Paralle 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
 2.375 inches Distance Between Centerlines Of Mounting Facilities Paralla 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a 	
Distance Between Centerlines Of Mounting Facilities Paralle 2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping N/a	allel To Height:
2.375 inches Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	-
Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: G3 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	el To Body Width:
2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 50.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 70.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Bayonet latch Plastic all mating ends Shell Material: Plastic Included Contact Quantity: Ga 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a 	
 Nonremovable all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a 	
Contact Maximum Ac Voltage Rating In Volts: 500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
500.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Contact Maximum Dc Voltage Rating In Volts: 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
 700.0 all mating ends single contact grouping Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a 	
Connector Locking Method: Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Bayonet latch Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Insert Material: Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Plastic all mating ends Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Shell Material: Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Plastic Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Included Contact Quantity: 63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
63 2nd mating end all contact groupings Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Included Contact Type: Round socket all mating ends single contact grouping Shelf Life: N/a	
Round socket all mating ends single contact grouping Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Unit Of Measure: 	
Demilitarization:	
No	
Fiig:	
A039b0	