

View Online at <https://aerobasegroup.com/nsn/5935-00-500-5222>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling w/backshell

Overall Diameter:

1.469 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

22.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 1st contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid or split

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Conduit nut

Thread Length:

0.375 inches and 0.625 inches

Thread Size:

1.188 inches and 1.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

8 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surface silver

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0