NSN 5935-00-500-5456

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-500-5456 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Square flange mount **Overall Length:** 2.060 inches **Mounting Hole Circle Radius:** 0.750 inches **Overall Diameter:** 3.310 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 975.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1365.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Thread Size:** 0.164 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:**

24 single mating end single contact grouping

NSN 5935-00-500-5456

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Flat pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material:
Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0