Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-500-8678

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Thru-hole mount
Overall Length:
1.119 inches
Bushing Diameter:
Between 1.136 inches and 1.156 inches
Overall Diameter:
1.250 inches
Environmental Protection:
Hermetic
Distance From Mounting Shoulder To Rear Face:
0.838 inches
Mounting Facility Thickness:
0.062 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
14 number 16 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18



Thread Size: 1.250 inches and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Steel single mating end single contact grouping **Contact Surface Treatment:** Tin single mating end single contact grouping **Insert Material:** Glass single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping Shell Material: Steel **Shell Surface Treatment:** Tin **Included Contact Quantity:** 14 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round socket single mating end single contact grouping **Special Features:** Thru-hole, solder or brazed mounting **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0