Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-500-9257

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.009 inches	
Overall Height:	
0.954 inches	
Overall Width:	
0.954 inches	
Environmental Protection:	
Moisture resistant and vibration resistant and salt water r	esistant
Unthreaded Mounting Hole Diameter:	
Between 0.115 inches and 0.130 inches	
Center To Center Distance Between Mounting Facilit	ies Parallel To Height:
0.719 inches	
Distance Between Centerlines Of Mounting Facilities	Parallel To Body Width:
0.719 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.442 inches and 0.447 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
10-13 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet pin	
Thready Qty Per Inch (tpi):	
24	
Thread Size:	
0.562 inches	

Electrical Receptacle Connector - Page 2 of 2



## Terminal Location:

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

### Shell Surface Treatment:

Cadmium and chromate

### **Included Contact Quantity:**

13 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.013 gold grains, troy and 0.013 silver grains, troy

**Precious Material:** 

Gold and silver

## **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unef

## **Specification Data:**

81349-mil-c-38999 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0