## NSN 5935-00-500-9618

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-500-9618

Body Style:
Straight shape
Overall Length:
0.954 inches
Overall Height:
3.110 inches
Overall Width:
2.000 inches
Environmental Protection:
Moisture resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 2.778 inches and 2.788 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.432 inches and 1.442 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
67 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 2nd mating end 2nd contact grouping
Polarization Method:
1 polarization post
Shell Type:
Solid
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end all contact groupings
Guide Design And Location:
Hexagon shape male post right-hand at 6 oclock
Shell Material:

## NSN 5935-00-500-9618

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
64 2nd mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Polarization post at position 91
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.134 gold grains, troy and 0.134 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0