Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-501-1668

## Body Style:

Straight shape

# **Overall Length:**

Between 2.714 inches and 2.744 inches

## **Overall Height:**

Between 0.416 inches and 0.436 inches

#### **Overall Width:**

Between 0.479 inches and 0.509 inches

## **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

## Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

## Mating End Quantity:

**Contact Position Arrangement Style:** 

37 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Polarization Method:**

Mating end

Shell Type:

Solid

1

# **Connector Locking Method:**

Friction

# **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

# **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Metal

# NSN 5935-00-501-1668

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium and chromate

#### Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

## Insert Material Specification:

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification

2nd material response single mating end

#### **Included Contact Quantity:**

37 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.037 gold grains, troy

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-24308/7 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.