

View Online at <https://aerobasegroup.com/nsn/5935-00-501-5682>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

0.750 inches

**Overall Diameter:**

0.375 inches

**Environmental Protection:**

Watertight

**Cable Entrance Diameter:**

0.090 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Mb single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Special Features:**

Blue grummet

**Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0