NSN 5935-00-501-5712

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-501-5712

Body Style: Rectangular shape **Overall Length:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.687 inches **Overall Height:** 0.781 inches **Overall Width:** 0.750 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.469 inches **Mating End Quantity: Contact Position Arrangement Style:** Err-090 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate mineral filled single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Solder well single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-00-501-5712

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 34 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Brass cllindrical guides **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.034 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Fiig:

No

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.