Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-501-7256

| Th | iread Class: |
|-----|---|
| 2a | |
| Th | read Direction: |
| Ri | ght-hand |
| 0 | verall Length: |
| 0.5 | 531 inches |
| 0 | verall Diameter: |
| 0.7 | 719 inches |
| Th | readed Device Type: |
| Mo | punting bushing |
| Ma | ating End Quantity: |
| 1 | |
| Co | ontact Removability: |
| No | prremovable single mating end single contact grouping |
| Co | onnector Locking Method: |
| La | tch |
| Th | ready Qty Per Inch (tpi): |
| 20 | |
| Th | read Size: |
| 0.5 | 500 inches |
| In | sert Material: |
| Pla | astic single mating end |
| In | cluded Contact Quantity: |
| 9 : | single mating end single contact grouping |
| Βι | Ishing Accommodation Hole Shape: |
| Ro | bund |
| In | cluded Contact Type: |
| Ro | ound pin single mating end single contact grouping |
| Th | read Series Designator: |
| Ur | ıf |
| Sł | nelf Life: |
| N/ | a |
| Ur | nit Of Measure: |
| | |
| De | emilitarization: |
| No | |
| Fii | g: |
| AC | J39b0 |