NSN 5935-00-501-7366



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-501-7366 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.855 inches **Overall Height:** 0.244 inches **Overall Width:** 0.260 inches **Distance Between Mounting Facility Centers:** 0.625 inches **Threaded Device Type:** Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

14 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

8 single mating end single contact grouping

NSN 5935-00-501-7366

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Round socket single mating end single contact grouping

Special Features:

Removed pins f-j-k-b-d-h

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0