Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-501-8282

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape center screwlock
Overall Length:
2.164 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.700 inches
Overall Height:
1.139 inches
Overall Width:
0.890 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and moisture resistant and salt water resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1 Contest Removability
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
2 polarization posts
Connector Locking Method:
Jackscrew
Thready Qty Per Inch (tpi):
32 Thread Since
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c or d, class 1 military specification 1st treatment response single mating end single contact grouping and

qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping



Terminal Type:	moting and single contact grouping
	mating end single contact grouping
Contact Material	-
	sition a federal specification single material response single mating end single contact grouping
Guide Design Ar	
	emale post right-hand at 9 oclock
Insert Material S	
	pecification single material response single mating end
Included Contac	-
	end single contact grouping
Included Contac	
	ngle mating end single contact grouping
Precious Materia	
Contact surfaces	
Precious Materia	-
0.055 gold grains	, troy
Precious Materia	al:
Gold	
Thread Series De	esignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure	:
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military	Standard):
Mil-g-45204 spec	