# NSN 5935-00-501-8317

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-501-8317

View Offline at https://acrobasegroup.com/nsn/0900-001-001/
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape center screwlock
Overall Length:
2.164 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.700 inches
Overall Height:
1.139 inches
Overall Width:
0.890 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and moisture resistant and salt water resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
2 polarization posts
Connector Locking Method:
Jackscrew
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c or d, class 1 military specification 1st treatment response single mating end single contact grouping and
qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

## NSN 5935-00-501-8317

Electrical Receptacle Connector - Page 2 of 2



## **Terminal Type:**

Wire wrap single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750, composition a federal specification single material response single mating end single contact grouping

## **Guide Design And Location:**

Hexagon shape female post right-hand at 5 oclock

## **Insert Material Specification:**

L-p-410 federal specification single material response single mating end

## **Included Contact Quantity:**

55 single mating end single contact grouping

#### **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.055 gold grains, troy

#### **Precious Material:**

Gold

## **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

## **Unit Of Measure:**

\_

## **Demilitarization:**

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.