## NSN 5935-00-501-9164

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-501-9164

Body Style:
Hood, top opening w/clamp
Overall Length:
1.250 inches
Overall Height:
1.625 inches
Overall Width:
0.688 inches
Cable Entrance Diameter:
0.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
8 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
730.0 single mating end single contact grouping
Polarization Method:
Polarization Method: Contact
Contact
Contact Shell Type:
Contact Shell Type: Hood, top opening
Contact Shell Type: Hood, top opening Connector Locking Method:
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method:
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment:
Contact  Shell Type: Hood, top opening  Connector Locking Method: Spring friction  Connector Cable Strain Relief Method: Cable clamp  Terminal Location: Back single mating end single contact grouping  Contact Surface Treatment: Cadmium single mating end single contact grouping
Contact  Shell Type: Hood, top opening  Connector Locking Method: Spring friction  Connector Cable Strain Relief Method: Cable clamp  Terminal Location: Back single mating end single contact grouping  Contact Surface Treatment: Cadmium single mating end single contact grouping  Insert Material:
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type:
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping
Contact Shell Type: Hood, top opening Connector Locking Method: Spring friction Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Cadmium single mating end single contact grouping Insert Material: Plastic phenolic single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Surface Treatment:

Included Contact Type:

Flat socket single mating end single contact grouping

## NSN 5935-00-501-9164

Electrical Plug Connector - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0