Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-502-0072

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, flange mount, external coupling
Overall Length:
2.000 inches
Overall Height:
2.010 inches
Overall Width:
2.010 inches
Environmental Protection:
Moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.142 inches and 0.157 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.557 inches and 1.567 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.557 inches and 1.567 inches
Distance From Mounting Shoulder To Front Face:
Between 0.812 inches and 0.828 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-15 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Potting



Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Potting type
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Rubber single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
35 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.035 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0