NSN 5935-00-502-0918

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-502-0918

| Body Style: |
|--|
| Straight shape |
| Overall Length: |
| 3.594 inches |
| Overall Height: |
| 0.594 inches |
| Overall Width: |
| 1.375 inches |
| Distance Between Mounting Facility Centers: |
| 2.844 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 15.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 125.0 single mating end single contact grouping |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Screw single mating end single contact grouping |
| Included Contact Quantity: |
| 2 single mating end single contact grouping |
| Included Contact Type: |
| Flat socket single mating end single contact grouping |
| Special Features: |
| Furnished items - lock tab |
| Precious Material And Location: |

Contact surfaces gold

NSN 5935-00-502-0918

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Weight: |
|--------------------------------------|
| 0.002 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.