## NSN 5935-00-502-2532

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-502-2532

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

0.828 inches

**Overall Height:** 

Between 1.297 inches and 1.328 inches

**Overall Width:** 

Between 1.297 inches and 1.328 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.963 inches and 0.973 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.963 inches and 0.973 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.422 inches and 0.453 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

24 number 20 24 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Bayonet latch

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-502-2532

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize or chromium
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
0 ring added under coupling ring
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.024 gold grains, troy and 0.024 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0