

View Online at <https://aerobasegroup.com/nsn/5935-00-502-4323>

**Body Style:**

Hood, top opening w/clamp

**Overall Width:**

1.275 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Cable Entrance Diameter:**

0.625 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Insert Material Specification:**

Mil-m-14, type mdg military specification single material response single mating end

**Included Contact Quantity:**

32 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.032 gold grains, troy and 0.032 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.