NSN 5935-00-502-4369

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-502-4369

| view Online at https://derobasegroup.com/nsi//3335-00-302-4303 |
|--|
| Body Style: |
| Straight shape, internal coupling w/backshell |
| Overall Length: |
| 1.088 inches |
| Overall Diameter: |
| 1.335 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 7p single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |

Contact surfaces gold

Precious Material And Location:

NSN 5935-00-502-4369

Electrical Plug Connector - Page 2 of 2



| Precious Material And Weight: |
|--------------------------------------|
| 0.007 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.