NSN 5935-00-502-9220

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-502-9220 **Thread Class:** 2b **Thread Direction:** Right-hand **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 40 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 875.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1225.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Included Contact Quantity:** 40 single mating end single contact grouping **Included Contact Type:**

Round pin single mating end single contact grouping

Unc

Thread Series Designator:

NSN 5935-00-502-9220

Electrical Receptacle Connector - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0