## NSN 5935-00-503-3992

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-503-3992

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.340 inches

**Overall Diameter:** 

1.197 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Distance From Mounting Shoulder To Front Face:** 

0.778 inches

**Mounting Facility Thickness:** 

0.125 inches

**Threaded Device Type:** 

Back shell and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

"10-5, 10-05" single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

280.0 and 242.0 and 130.0 and 48.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

Thready Qty Per Inch (tpi):

28 and 20

**Thread Size:** 

0.625 inches and 0.750 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-00-503-3992

Electrical Receptacle Connector - Page 2 of 2



## Contact Surface Treatment Specification: Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Shell Material:

**Shell Surface Treatment:** 

Aluminum alloy 6061

Chromium

**Shell Material Specification:** 

Qq-a-367, t6 federal specification single material response

**Included Contact Quantity:** 

5 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.025 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Un and unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.